



Kyocera Technology

› PRINT › COPY › SCAN › FAX

CS 3011i

BLACK & WHITE  
MULTIFUNCTIONAL SYSTEM

# POWERFUL PERFORMANCE... CONNECTING PEOPLE AND INFORMATION.



The Copystar CS 3011i Black and White MFP brings impressive performance to power your document needs. Print, Copy and Color Scan capabilities, along with advanced finishing options, deliver fast, professional output. A customizable 9" color touch screen offers easy access directly from the MFP to a wide array of flexible features and business applications to optimize workflow, while wireless and remote access capabilities ensure vital information is easily retrievable no matter where your business takes you.

- › Crisp Black and White Output up to 30 Pages per Minute
- › Customizable 9" Color Touch Screen with Intuitive, Tablet-Like Home Screen

- › Robust Portfolio of Business Applications that Can Optimize Your Document Workflow
- › Advanced Finishing Options for Professional Output, including a 1,000-Sheet External Finisher
- › Scalable Paper Capacity for Longer Job Runs
- › Flexible Media Support and Paper Sizes up to 11" x 17"
- › Standard USB Host Interface for On-the-Go Printing and Scanning
- › Efficient Color Scanning up to 160 ipm
- › Convenient Wireless Printing and Scanning
- › Apple AirPrint®, Google Cloud Print™ and KYOCERA Mobile Print Compatible for a Mobile Printing Solution



Kyocera Technology

**BASIC SPECIFICATIONS**

**Configuration:** Black and White Multifunctional System – Print/Scan/Copy/Optional Fax

**Pages Per Minute:** Letter: 30 ppm, Legal: 15 ppm, Ledger: 15 ppm

**Warm Up Time:** 18 Seconds or Less (Power On)

**First Page Out:** Copy: 3.6 Seconds or Less; Print: 4.2 Seconds or Less

**Display:** 9" Color Touch Screen Control Panel

**Resolution / Bit Depth:** 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth

**Memory / Hard Disk Drive:** 2 GB RAM / 8 GB SSD / 320 GB HDD Standard

**Duplex:** Standard Stackless Duplex Supports Statement to Ledger (5.5" x 8.5" – 11" x 17"), 16 lb Bond – 140 lb Index (60 – 160gsm)

**Standard Output Tray:** Statement - 11" x 17"; 250 Sheets

**Electrical Requirements:** 120V, 60Hz, 11.6A; 220-240V, 50Hz, 6.3A

**Typical Electricity Consumption (TEC):** 120V: 1.8 kWh/week; 220V: 1.8 kWh/week

**Dimensions / Weight:** 23.39" W x 27.40" D x 26.77" H / 127.9 lbs

**Maximum Monthly Duty Cycle:** 125,000 Pages Per Month

**PAPER SUPPLY****Standard Paper Sources:**

Dual 500 Sheet Trays, 100 Sheet MPT; Auto Selection/Switching

**Optional Paper Sources:**

Dual 500 Sheet Trays (PF-791), Dual 1,500 Sheet Trays (PF-810)

**Paper Capacity:**

Standard: 1,100 Sheets; Maximum: 4,100 Sheets

**Paper Size:** Trays 1, 2 and (PF-791): 5.5" x 8.5" – 11" x 17";

(PF-810): 8.5" x 11"; MPT: 5.5" x 8.5" – 11" x 17" (Multiple Sheets)

**Paper Weight:**

Trays: 16 lb Bond – 90 lb index (60 – 163gsm);

MPT: 12 lb Bond – 140 lb Index (45 – 256gsm)

**Input Materials:**

Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes

**SECURITY SPECIFICATIONS**

**Standard:** Local Authentication, Network Authentication (IPsec, HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL); Scan to e-mail (POP3/SMTP over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; SSL

**Optional:** Data Security Kit (E): Network Data Encryption, HDD Overwrite Mode, HDD Data Encryption

**PRINT SPECIFICATIONS**

**Standard Controller:** Freescale QorIQ T1024 (Dual Core) / 1.0GHz

**PDLs / Emulations:**

Standard: PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS;

Optional: UG-34 IBM ProPrinter, Line Printer, LQ-850

**Print Resolution:** 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth

**Fonts:** 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap

**Windows OS Compatibility:** Windows XP/2003/Vista/2008/7/8/10/Server 2008 R2/Server 2012 R2

**Novell OS Compatibility:** Novel NetWare 3.x/4.x/5.x/6.x

**Mac OS Compatibility:** OS 10.x, AirPrint Enabled

**UNIX OS Compatibility:** Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX(LPR)

**Mobile Printing:** Apple AirPrint®, Google Cloud Print™, KYOCERA Mobile Print

**Interfaces:** Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0,

4 USB Host Interfaces, 2 Expansion Slots

Optional: 10/100/1000BaseTX (IB-50 for Dual NIC);

Optional: IEEE 802.11 b/g/n (IB-51 for Wireless LAN Interface)

**Network Print and Supported Protocols:** TCP/IP, NetBEUI, FTP, LPR, IPv6, IPsec, SSL, WSD Print

**Drivers:** KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver,

Network Fax Driver, PPD for MAC

**Utilities:** KYOCERA Net Admin, KYOCERA Net Viewer, PDF Direct

Print, Command Center RX

**SCAN SPECIFICATIONS**

**Scan Type:** Color and Black & White Scanner

**Scan Resolution:** 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi

**File Formats:** TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG

**PDF Extension:** Searchable PDF (OCR) Option

**Scan Speeds:**

**DP-7120:** Simplex: 48 ipm B&W / 48 ipm Color (300 dpi);

Duplex: 15 ipm B&W / 15 ipm Color (300 dpi)

**DP-7100:** Simplex: 80 ipm B&W / 80 ipm Color (300 dpi);

Duplex: 48 ipm B&W / 48 ipm Color (300 dpi)

**DP-7110:** Simplex: 80 ipm B&W / 80 ipm Color (300 dpi);

Duplex: 160 ipm B&W / 160 ipm Color (300 dpi)

**Connectivity / Supported Protocols:** 10/100/1000BaseTX, TCP/IP,

Hi-Speed USB 2.0

**Scanning Functions:** Scan to Folder (SMB), Scan to e-Mail, Scan to

FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

**Original Size:**

Through DP: Statement to Ledger (5.5" x 8.5" – 11" x 17");

Glass: up to 11" x 17"

**Drivers:** TWAIN Driver, WIA Driver

**COPY SPECIFICATIONS**

**Copy Resolution:** 600 x 600 dpi

**Image Mode:** Text, Photo, Text/Photo, Graphic/Map

**Continuous Copy:** 1-999/ Auto Reset to 1

**Additional Features:** Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip

**Job Management:** 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy

**Magnification / Zoom:** Full Size, 4 Reduction, 4 Enlargement

Preset Ratios, 25 - 400% in 1% step increments

**Document Box:** Custom Box, Job Box, Removable Memory Box,

Fax Box (with optional Fax System)

**DOCUMENT PROCESSOR<sup>1</sup>****Type / Capacity:**

**DP-7120:** Reversing Automatic Document Processor / 50 Sheets

**DP-7100:** Reversing Automatic Document Processor / 140 Sheets

**DP-7110:** Dual Scan Document Processor / 270 Sheets

**Acceptable Originals:** 5.5" x 8.5" – 11" x 17"

**Acceptable Weights (Simplex / Duplex):**

**DP-7120:** Simplex: 13 - 32 lb Bond (45 – 160gsm);

Duplex: 13 - 32 lb Bond (50 – 120gsm)

**DP-7100:** Simplex: 13 lb Bond - 90 lb Index (35 – 160gsm);

Duplex: 16 lb – 32 lb Bond (50 – 120gsm)

**DP-7110:** Simplex: 13 lb Bond – 120 lb Index (35 – 220gsm);

Duplex: 16 lb – 120 lb Index (50 – 220gsm)

**FAX SPECIFICATIONS (OPTION)**

**Fax Type:** Fax System 12

**Compatibility / Data Compression:** G3 Fax / MMR, MR, MH, JBIG

**Transmission Speed / Modem Speed:** Approximately 3 seconds per page / 33.6 Kbps

**Fax Memory:** Standard 170 MB

**Driver:** Network Fax Driver

**Fax Functions:** Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax

**OPTIONAL 1,000 SHEET FINISHER DF-7120<sup>3</sup>**

**Stack / Staple Capacity:** Main Tray: 1,000 Sheets / 50 Sheets (up to 24 lb Bond 90gsm)

**Paper Size:** 5.5" x 8.5" – 11" x 17"

**Paper Weight:** 16 lb Bond – 140 lb Index (60 – 256gsm)

**Edge Staple Position:** 3 Positions: Top Left, Bottom Left,

Center Bind

**Optional Punch:** PH-7A 2 and 3 Hole Punch Unit, Supports

8.5" x 11" – 11" x 17", 13 lb Bond – 93 lb Cover (45 – 256gsm)

**Dimensions:** 21.57" W x 24.35" D x 41.34" H

**OPTIONAL 3,000 SHEET FINISHER DF-791<sup>2,3</sup>**

**Stack / Staple Capacity:** Main Tray: 3,000 Sheets; Sub Tray(B):

200 Sheets; Sub Tray(C): 50 Sheets / 65 Sheets: 8.5" x 11";

30 Sheets: 8.5" x 14", 11" x 17"

**Paper Size:** Main Tray: 8.5" x 11" – 11" x 17";

Sub Tray(B): 5.5" x 8.5" – 11" x 17"

**Paper Weight:** 16 lb Bond – 140 lb Index (60 – 256gsm)

**Edge Staple Position:** 3 Positions: Top Left, Bottom Left,

Center Bind

**Optional Punch:** PH-7A 2 and 3 Hole Punch Unit, Supports

8.5" x 11" – 11" x 17", 13 lb Bond – 93 lb Cover (45 – 256gsm)

**Dimensions:** 23.91" W x 26.32" D x 37.45" H

**Optional Multi-Bin Mailbox<sup>4</sup>: MT-730(B)** includes 7 Trays;

Supports 16 lb Bond – 90 lb Index (60 – 163gsm); Stack

Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11";

50 Sheets: 8.5" x 14", 11" x 17"

**ADDITIONAL OPTIONS**

**AK-740** (Bridge Unit for Finisher), **IB-50** Gigabit NIC (Dual NIC),

**IB-51** Wireless LAN, Card Authentication Kit (B), Cabinet, Card

Reader Holder(E), Keyboard Holder (B), Data Security Kit (E),

Scan Extension Kit (A) for Searchable PDF/OCR

<sup>1</sup> Only 1 Document Processor can be installed

<sup>2</sup> Only 1 Output Option can be installed

<sup>3</sup> Requires Bridge Unit Attachment Kit (AK-740)

<sup>4</sup> Requires DF-791

**ONLY FROM KYOCERA**

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability.

Looking to streamline your document workflow? KYOCERA offers a robust portfolio of Business Applications that seamlessly and securely integrate with our MFPs. To learn more about which Business Applications are right for your business, visit the Solutions section on our website.

Specifications and design are subject to change without notice.

For the latest on connectivity visit [www.copystar.com](http://www.copystar.com)

MAC and AirPrint are trademarks of Apple, Inc.

Google Cloud Print is a trademark of Google, Inc.

PRESCRIBE, KX Driver, and Command Center RX are the trademarks of The Kyocera Companies.

All other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc.

Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA

©2016 KYOCERA Document Solutions America, Inc.

IC# 855D400474

