

FS-9530DN

Document Imaging Solution

WORK HARD. PRINT SMART.



- ▶ Fast Output Speed of 51 Pages per Minute
- Standard Network Interface
- Standard Duplex
- ▶ Standard 1,200 Sheet Paper Capacity
- Optional Paper Handling and Finishing
- ▶ USB Host Printing for Convenient PDF Output
- Optional Data Security Kit for Added Document Security
- Secure Printing and Job Storage
- Long Life Consumables



FS-9530DN SPECIFICATIONS

Configuration: Enterprise Network Monochrome Printer with Standard Duplex, 500 x 2 Sheet Paper Drawers and 200 Sheet Multipurpose Tray, Optional Paper Handling and Advanced Finishing. Resolution: 600 x 600 DPI; Fast 1200 Print Mode; 300 x 300 DPI Printer Memory: Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMs, Standard CF Card Slot(Type 1); Optional HDD Electrical Requirements: 120V, 60Hz, 11.4A Dimensions: 23.6°W x 25.4°D x 24.2°H Weight: 150 lbs Max Duty Cycle: 300,000 Pages per Month CONTROLLER SPECIFICATIONS: CPU/MHz: PowerPC750FL/600 MHz Supported PDL/Emulations: PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson L0850, Line Printer 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/KL, 1 Bitmap Font Windows® OS Compatibility: Windows® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell NetWare® 3.x/4.x/5.x/6.x UNIX OS Compatibility: Vinture Standard 10/100 Base IX, Hi-Speed USB 2.0, Bi-Directional Parallel EEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/P, PIX/SPX, AppleTalk, NetBEUI Oriver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT 515" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" x 11.7" x 17.7" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS:	BASIC SPECIFICATION	S:
Resolution: 600 x 600 DPI; Fast 1200 Print Mode; 300 x 300 DPI Printer Memory: Standard 128MB, Upgradeable to 6,40MB via 100 Pin DDR DIMMs, Standard CF Card Slott(Type 1); Optional HDD Electrical Requirements: 120V, 60Hz, 11,4A Dimensions: 23.6 "W x 25.4" D x 24.2" H Weight: 150 lbs Max Duty Cycle: 300,000 Pages per Month CONTROLLER SPECIFICATIONS: CPU/MHz: PowerPC750FL/600 MHz Supported PDL/Emulations: PRESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell Netware® 3,x/4,x/5,x/6,x UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR) UNIX OS Compatibility: OS 4.1x; Solaris 2.x; AIX, HP-UX (LPR)		Enterprise Network Monochrome Printer with Standard Duplex, 500 x 2 Sheet Paper Drawers
Resolution: 300 x 300 DPI Printer Memory: Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMs, Standard CF Card Slot(Type 1); Optional HDD Electrical Requirements: 120,6 60Hz, 11.4A Dimensions: 23,6 "W x 25,4"D x 24,2"H Weight: 150 lbs Max Duty Cycle: 300,000 Pages per Month CONTROLLER SPECIFICATIONS: CPU/MH2: PowerPC750FL/600 MHz CPU/MH2: PowerPC750FL/600 MHz Supported PDI/Emulations: Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5 c/KL, 1 Bitmap Font Windows® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell NetWare® 3.x/4,x/5,x/6.x UNIX OS Compatibility: UNIX OS Compatibility: VS un OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Ustom: 3.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Ustom: 3.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warn-Up Time: Less than 6.5 Seconds		
300 x 300 DP	Resolution:	
Printer Memory: Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMS, Standard CF Card Slot(Type 1); Optional HDD Electrical Requirements: 120V, 60Hz, 11.4A Dimensions: 23.6"W x 25.4"D x 24.2"H Weight: 150 lbs Max Duty Cycle: 300,000 Pages per Month CONTROLLER SPECIFICATIONS: CPUJ/MH2: PowerPC750FL/600 MHZ Supported PDI/Emulations: PRESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Windows® 0S Compatibility: Windows® 0S Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Sun OS 4,1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/P, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utillities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/a,200 Paper Weight: 6 - 28 lb Bond via Paper Drawers, 13 lb Bond, 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds	Resolution.	
Dimensions: 23.6 "W x 25.4" D x 24.2" H Weight: Nax Duty Cycle: 300,000 Pages per Month CONTROLLER SPECIFICATIONS: CPU/MH2: PowerPC750FL/600 MHz Supported PDL/Emulations: RCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/KL, 1 Bitmap Font Windows® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell Nos Compatibility: Novell® OS Compatibility: Novell Nos Compatibility: Novell NetWare® 3.x/4.x/5.x/6.x OS 10.x UNIX OS Compatibility: Sun OS 4,1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Whole Interface: Whole Machael Standard Center Utilities: PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", 43.4, 44, 5, 84, 85 Custom: 3.5" x 5.8" 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Embedded Stackless Duplex Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Embedded Stackless Duplex Paper Weight: 16 - 28 lb Bond via Paper Drawers, 14", 11" x 17", 44, 45, 85 Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warn-Up Time: Less than 60 Seconds First Print Out: Less than 3,5 Seconds	,	Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMs, Standard CF Card
Weight: Max Duty Cycle: 300,000 Pages per Month	Electrical Requirements:	120V, 60Hz, 11.4A
Max Duty Cycle: 300,000 Pages per Month CONTROLLER SPECIFICATIONS: PowerPC750FL/600 MHz Supported PDL/Emulations: RESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Windows® 95/98/Me/2000/XP/2003/Windows 7 Novell® OS Compatibility: Windows® 95/98/Me/2000/XP/2003/Windows 7 Novell® OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) Connectivity/Interface: Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: Kyocera Command Center Utilities: Kyocera Command Center Utilities: Soo x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Dimensions:	23.6"W x 25.4"D x 24.2"H
CONTROLLER SPECIFICATIONS: CPU/MHz: PowerPC750FL/600 MHz Supported PDL/Emulations: RCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: UNIX OS Compatibility: Sun OS 4,1.x; Solaris 2.x; AIX, HP-UX (LPR) Connectivity/Interface: Sun OS 4,1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Wyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Prawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 Ib Bond via Paper Drawers, 13 Ib Bond - 110 Ib Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 Ib Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Weight:	150 lbs
CPU/MHz: Supported PDL/Emulations: RESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Windows® OS Compatibility: Novell® OS Compatibility: Novell® OS Compatibility: Novell NetWare® 3.x/4.x/5.x/6.x Mac OS Compatibility: UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: CP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Wyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Max Duty Cycle:	300,000 Pages per Month
Supported PDL/Emulations: RESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Windows® 95/98/Me/2000/XP/2003/Windows 7 Novell® OS Compatibility: Novell NetWare® 3.x/4.x/5.x/6.x UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	CONTROLLER SPECIFI	CATIONS:
Supported PDL/Emulations: RESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer Fonts: 136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Windows® 95/98/Me/2000/XP/2003/Windows 7 Novell® OS Compatibility: Novell NetWare® 3.x/4.x/5.x/6.x UNIX OS Compatibility: OS 10.x UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	CPU/MHz:	PowerPC750FL/600 MHz
for PCL 5c/XL, 1 Bitmap Font Windows® OS Compatibility: Windows® 95/98/Me/2000/XP/2003/Windows 7 Novell® OS Compatibility: OS 10.X Mac OS Compatibility: Sun OS 4.1.X; Solaris 2.X; AIX, HP-UX (LPR) Connectivity/Interface: Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", 44, 45, 85 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		PRESCRIBE, PCL6 (PCL XL,PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 63o, IBM ProPrinter X24, Epson LQ85o, Line Printer
Novell® OS Compatibility: Mac OS Compatibility: UNIX OS Compatibility: Connectivity/Interface: Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Fonts:	
Mac OS Compatibility: UNIX OS Compatibility: Connectivity/Interface: Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
UNIX OS Compatibility: Connectivity/Interface: Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® (64-bit Drivers) Web Interface: Web Interface: Web Interface: Web Interface: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Connectivity/Interface: Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
Bi-Directional Parallel IEEE1284, USB Host (Full Speed) KUIO LV Expansion Slots (2): Optional Hard Disk Drive Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
Optional IB-23 Network Interface Supported Protocols: TCP/IP, IPX/SPX, AppleTalk, NetBEUI Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		Bi-Directional Parallel IEEE1284, USB Host (Full Speed)
Driver: KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	KUIO LV Expansion Slots (2):	
for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers Web Interface: Kyocera Command Center Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Supported Protocols:	
Utilities: KMnet Admin, KMnet Viewer, PDF Direct Print, PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers
PRESCRIBE Utilities PAPER SUPPLY: Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
Standard Paper Sources: 500 x 2 Sheet Drawers, 200 Sheet MPT Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Utilities:	
Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	PAPER SUPPLY:	
Drawer Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17" MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Standard Paper Sources:	500 x 2 Sheet Drawers, 200 Sheet MPT
MPT Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5 Custom: 3.5" x 5.8" - 11.7" x 17.7" Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
Std/Max Paper Capacity: 1,200/4,200 Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	MPT Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A3, A4, A5, B4, B5
Paper Weight: 16 - 28 lb Bond via Paper Drawers, 13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Custom:	3.5" x 5.8" - 11.7" x 17.7"
13 lb Bond - 110 lb Index via MPT Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
Input Materials: Bond, Recycled, Transparencies, Labels, Envelopes, High Quality STANDARD DUPLEX: Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Paper Weight:	
Type: Embedded Stackless Duplex Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Input Materials:	Bond, Recycled, Transparencies, Labels,
Paper Size: 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	STANDARD DUPLEX:	
A4, A5, B5 Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds		
Paper Weight: 16 - 21 lb Bond OUTPUT SPEEDS: Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Paper Size:	
Warm-Up Time: Less than 60 Seconds First Print Out: Less than 3.5 Seconds	Paper Weight:	
First Print Out: Less than 3.5 Seconds		
Pages Per Minute: 51 Letter, 31 Legal, 26 Ledger		
	Pages Per Minute :	51 Letter, 31 Legal, 26 Ledger

Paper Capacity:	VERS: PF-700 500 x 2 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17
Dimensions/Weight:	23.0"W x 23.2"D x 12.4"H/57.3 lbs
Large Capacity T	RAY: PF-750
Paper Capacity:	3,000 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" X 11"
Dimensions/Weight:	23.0"W x 23.6"D x 12.4"H/50.7 lbs
FINISHER: DF-710	
Stack Capacity:	Main Tray (A): 3,000 Sheets; Sub Tray (B): 200 Sheets; Sub Tray (C): 50 Shee
Paper Size:	Main Tray (A): 8.5" x 11" - 11" x 17"; Sub Tray (B): 5.5" x 8.5" - 11" x 17";
Papar Waight	Sub Tray (C): 5.5" x 8.5", 8.5" x 11", 12 lb Bond - 110 lb Index
Paper Weight: Staple Capacity:	50 Sheets: 8.5" x 11";
Staple Capacity:	30 Sheets: 8.5
Edge Staple Position:	3 Positions: Top Left, Bottom Left, Center Bi
Punch:	Optional 2 and 3 Hole
Saddle Stitch/Fold:	Optional Booklet Folder
Dimensions/Weight:	26.9"W x 22.2"D x 42.8"H/121 lbs
MULTI-TRAY: MT-7 Number of Trays:	7
Tray Capacity:	100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"
Paper Weight:	17 - 21 lb Bond
Dimensions/Weight:	20.1"W x 15.7"D x 18.5"H/22 lbs
Punch Unit: PH-5	
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	17 lb Bond – 110 lb Index
Number of Holes:	2 and 3
Weight:	6.6 lbs
BOOKLET FOLDER:	
Folding Capacity:	1 – 16 Sheets
Stack Capacity:	1-3 Sheets - 30 Booklets; 4-6 Sheets - 20
Donar Ciao	Booklets; 7-16 Sheets - 10 Booklets
Paper Size: Paper Weight:	8.5" X 11", 8.5" X 14", 11" X 17"
raper weight:	16 lb Bond — 110 lb Index, Over 20 lb is one sheet only
Dimensions/Weight:	25.7"W x 17.9"D x 10.5"H/46.3 lbs
SIMPLE FINISHER:	
Stack Capacity:	8.5" x 11" - 1.000 Sheets:
Paper Size:	8.5" x 14", 11" x 17" - 500 Sheets 8.5" x 11" - 11" x 17"
Paper Weight:	17 - 34 lb Bond
	30 Sheets: 8.5" x 11";
Staple Capacity:	20 Sneets: 8.5 × 14 . 11 × 17
Edge Staple Position:	20 Sheets: 8.5" x 14", 11" x 17" 1 Position: Top Left

Enables Document Printing and e-MPS Functions:

Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual Mailboxes

Additional Options:

Data Security Kit (C); Printer Memory: 128, 256, 512MB RAM; Finisher Attachment Kit; Stand

CONSUMABLES:

TK-712: 40,000 pages @ 5% Coverage*

* Ships with 20,000 pages @ 5% Coverage. ISO19752 Certified

PAPER HANDLING OPTIONS:



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceradocumentsolutions.com. All trademarks and trade names are the property of their respective owners.

KYOCERA Document Solutions America, Inc. Headquarters: 225 Sand Road, PO Box 40008,







